



VP-MKS

Off-Grid Inverter

- Built-in MPPT solar charge controller
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current based on applications
- Configurable AC/Solar input priority via LCD setting
- Compatible to mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function
- Parallel operation with up to 9 units only available for Axpert MKS 4KVA/5KVA*





VP-MKS

Off-Grid Inverter

MODEL	VP-MKS 1K-24	VP-MKS 1K-48	VP-MKS 2K-24	VP-MKS 3K-24	VP-MKS 3K-48	VP-MKS 4K	VP-MKS 5K
Rated Power	1000VA/800W	1000VA/1000W	2000VA/1600W	3000VA/2400W	3000VA/2400W	4000VA/3200W	5000VA/4000W
INPUT							
Voltage	230 VAC						
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)						
Frequency Range	50 Hz/60 Hz (Auto sensing)						
OUTPUT							
AC Voltage Regulation (Batt.Mode)	230VAC ± 5%						
Surge Pow er	2000VA	4000VA	6000VA	8000VA	10000VA		
Efficiency (Peak)	90% - 93%	93%					
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)						
Waveform	Pure sine wave						
BATTERY							
Battery Voltage	24 VDC	48 VDC	24 VDC	24 VDC	48 VDC	48 VDC	
Floating Charge Voltage	27 VDC	54 VDC	27 VDC	27 VDC	54 VDC	54 VDC Max: 58VDC (optional 64VDC, please check w ith sales)	
Overcharge Protection	31 VDC	62 VDC	31 VDC	31 VDC	62 VDC	60 VDC (optional 66VDC, please check w ith sales)	
SOLAR CHARGER & AC CHARGER							
Maximum PV Array Pow er	600 W	900 W	600 W	600 W	900 W	4000 W	
MPPT Range @ Operating Voltage	30 VDC ~ 66 VDC	60 VDC ~ 88 VDC	30 VDC ~ 66 VDC	30 VDC ~ 66 VDC	60 VDC ~ 88 VDC	60 VDC ~115 VDC	
Maximum PV Array Open Circuit Voltage	75 VDC	102 VDC	75 VDC	75 VDC	102 VDC	145 VDC	
Maximum Solar Charge Current	25A	18 A	25A	25A	18 A	80 A	
Maximum AC Charge Current	20 A	15 A	30 A	30 A	15 A	60 A	
Maximum Charge Current	45A	33 A	55 A	55 A	33 A	140A	
Maximum Efficiency				98%	98%		
Standby Pow er Consumption				2 W	2 W		
PHYSICAL							
Dimension, D X W X H (mm)				100 x 272 x 355	120 x 295 x 468		
Net Weight (kgs)	6.8		7.0	7.4		11.0	
OPERATING ENVIRONMENT							
Humidity	5% to 95% Relative Humidity(Non-condensing)						
Operating Temperature	0°C to 55°C						
Storage Temperature	-15°C to 60°C						

* There are charging current selection only available for 230VAC system.

Product specifications are subject to change without further notice