



# GCL-M6/72GD


Bifacial Dual Glass  
Monocrystalline Module

335-370W


Cell Type



5BB



MBB



**370W**

Maximum Power  
Output

**19.2%**

Maximum Module  
Efficiency

**0~+5W**

Power Output  
Guarantee



Ideal choice for large scale  
ground installation



High conversion efficiency due  
to top quality wafers and  
advanced cell technology



Selected encapsulating  
material and stringent  
production process control  
ensure the product is highly  
PID resistant and snail trails  
free



Additional safety, Fire class A  
certified



Withstand up to 1500V  
system voltage effectively  
reduce BOS cost



Sand blowing test, salt mist  
test and ammonia test passed  
to endure harsh environments


## Company Introduction

GCL System Integration Technology Co. Ltd (002506 Shenzhen Stock) (GCL System) is part of GOLDEN CONCORD Group (GCL) which is an international energy company specializing in clean and sustainable power production. The group, founded in 1990 now employs 30,000 people.

## GCL Delivers Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Fully automatic facility and world-class technology
- Rigorous quality control to meet the highest standard: ISO9001:2008, ISO 14001: 2004 and OHSAS: 18001 2007
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing test: IEC 61701, IEC 62716, DIN EN 60068-2- 68)
- Long term reliability tests
- 2\*100% EL inspection ensuring defect-free modules

## Linear Performance Warranty



10 Years Product Warranty 30 Years Linear Power Warranty

\* Please refer to GCL standard warranty for details

## Additional Insurance Backed by Swiss RE



\* Please refer to GCL for details

# GCL-M6/72GD

## GCL-Mars Series Bifacial Dual Glass Monocrystalline Module

335-370W

### Electrical Specification (STC\*)

Test Condition		Front	Rear	Front	Rear	Front	Rear	Front	Rear	Front	Rear	Front	Rear
Maximum Power	P <sub>max</sub> (W)	350	248	355	251	360	255	365	258	370	262	375	265
Maximum Power Voltage	V <sub>mp</sub> (V)	38.51	38.91	38.72	39.12	38.92	39.32	39.13	39.53	39.32	39.72	39.52	39.92
Maximum Power Current	I <sub>mp</sub> (A)	9.09	6.36	9.17	6.42	9.25	6.48	9.33	6.53	9.41	6.59	9.49	6.64
Open Circuit Voltage	V <sub>oc</sub> (V)	47.33	46.63	47.53	46.83	47.73	47.03	47.93	47.23	48.13	47.43	48.33	47.63
Short Circuit Current	I <sub>sc</sub> (A)	9.56	6.71	9.64	6.77	9.72	6.82	9.80	6.88	9.88	6.94	9.96	6.99
Module Efficiency	(%)	17.9	12.7	18.2	12.9	18.4	13.0	18.7	13.2	19.0	13.4	19.2	13.6
Power Output Tolerance	(W)	0~+5											

\* Irradiance 1000W/m<sup>2</sup>, Module Temperature 25°C, Air Mass 1.5

### Electrical Specification (NOCT\*)

Test Condition		Front	Rear	Front	Rear	Front	Rear	Front	Rear	Front	Rear	Front	Rear
Maximum Power	P <sub>max</sub> (W)	261.00	183.96	264.98	186.43	268.63	188.92	272.30	191.42	276.37	194.30	280.09	196.84
Maximum Power Voltage	V <sub>mp</sub> (V)	36.00	36.00	36.20	36.20	36.40	36.40	36.60	36.60	36.80	36.80	37.00	37.00
Maximum Power Current	I <sub>mp</sub> (A)	7.25	5.11	7.32	5.15	7.38	5.19	7.44	5.23	7.51	5.28	7.57	5.32
Open Circuit Voltage	V <sub>oc</sub> (V)	44.10	43.30	44.20	43.50	44.40	43.70	44.60	43.90	44.80	44.10	45.00	44.30
Short Circuit Current	I <sub>sc</sub> (A)	7.73	5.43	7.79	5.47	7.86	5.51	7.92	5.56	7.99	5.61	8.05	5.65

\* Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s

### Mechanical Data

Solar Cell Type	Mono P-type bifacial 156.75×156.75mm (6 inches)
Number of Cells	72 Cells (6×12)
Dimensions of Module L*W*H (mm)	1968×992×6mm
Weight (kg)	27 Kg
Front Side Glass	High transparency solar glass 2.5mm (0.13 inches)
Back Side Glass	High transparency solar glass 2.5mm (0.13 inches)
J-Box	IP68 Rated
Cable	Portrait: 200/75mm ; Landscape: 1750/1750mm
Wind/ Snow Load	2400Pa/5400Pa*
Connector	MC4 Compatible

\* For more details please check the installation manual of GCLSI

### Temperature Ratings

Nominal Operating Cell Temperature (NOCT)	44±2°C
Temperature Coefficient of I <sub>sc</sub>	+0.06%/°C
Temperature Coefficient of V <sub>oc</sub>	-0.30%/°C
Temperature Coefficient of P <sub>max</sub>	-0.39%/°C

### Maximum Ratings

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Max Series Fuse Rating	18A

### Optional

Connector: ☐ Original MC4

### Packaging Configuration


Module per box	30 pieces
Module per 40' container	660 pieces




Contact Us for More Information

website: [en.gclsi.com](http://en.gclsi.com) email: [gclsisales@gclsi.com](mailto:gclsisales@gclsi.com)


### Module Dimension




Back View



### U-I Curve at Different Temperature (350W)



### U-I/P-U Curve at Different Irradiation (350W)



CAUTION: READ INSTALLATION MANUAL BEFORE USING THE PRODUCT