




GCL-P6/60GW


Dual Glass
Polycrystalline Module

270-305W


Cell Type



5BB



MBB



305W

Maximum Power Output

18.5%

Maximum Module Efficiency

0~+5W

Power Output Guarantee



Ideal choice for large scale ground installation



High conversion efficiency due to top quality wafers and advanced cell technology



Selected encapsulating material and stringent production process control ensure the product is highly PID resistant and snail trails free



Additional safety, Fire class A certified



Withstand up to 1500V system voltage effectively reduce BOS cost



Sand blowing test, salt mist test and ammonia test passed to endure harsh environments


Company Introduction

GCL System Integration Technology Co. Ltd (002506 Shenzhen Stock) (GCL System) is part of GOLDEN CONCORD Group (GCL) which is an international energy company specializing in clean and sustainable power production. The group, founded in 1990 now employs 30,000 people.

GCL Delivers Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Fully automatic facility and world-class technology
- Rigorous quality control to meet the highest standard: ISO9001:2008, ISO 14001: 2004 and OHSAS: 18001 2007
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing test: IEC 61701, IEC 62716, DIN EN 60068-2- 68)
- Long term reliability tests
- 2*100% EL inspection ensuring defect-free modules

Linear Performance Warranty



* Please refer to GCL standard warranty for details

Additional Insurance Backed by Swiss RE



* Please refer to GCL for details

GCL-P6/60GW

GCL-Jupiter Series Dual Glass Polycrystalline Module

270-305W

Electrical Specification (STC*)

| | | | | | | | | | |
|------------------------|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| Maximum Power | P _{max} (W) | 270 | 275 | 280 | 285 | 290 | 295 | 300 | 305 |
| Maximum Power Voltage | V _{mp} (V) | 31.20 | 31.40 | 31.60 | 31.80 | 32.20 | 32.40 | 32.60 | 32.80 |
| Maximum Power Current | I _{mp} (A) | 8.65 | 8.76 | 8.86 | 8.96 | 9.01 | 9.10 | 9.20 | 9.30 |
| Open Circuit Voltage | V _{oc} (V) | 38.30 | 38.50 | 38.70 | 38.90 | 39.70 | 40.00 | 40.30 | 40.60 |
| Short Circuit Current | I _{sc} (A) | 9.29 | 9.38 | 9.46 | 9.54 | 9.69 | 9.74 | 9.79 | 9.84 |
| Module Efficiency | (%) | 16.4 | 16.7 | 17.0 | 17.3 | 17.6 | 17.9 | 18.2 | 18.5 |
| Power Output Tolerance | (W) | 0~+5 | | | | | | | |

* Irradiance 1000W/m², Module Temperature 25°C, Air Mass 1.5

Electrical Specification (NOCT*)

| | | | | | | | | | |
|-----------------------|----------------------|--------|--------|--------|--------|--------|--------|--------|--------|
| Maximum Power | P _{max} (W) | 201.72 | 205.16 | 209.33 | 212.82 | 216.65 | 220.03 | 223.74 | 227.49 |
| Maximum Power Voltage | V _{mp} (V) | 28.90 | 29.10 | 29.40 | 29.60 | 29.80 | 30.10 | 30.40 | 30.70 |
| Maximum Power Current | I _{mp} (A) | 6.98 | 7.05 | 7.12 | 7.19 | 7.27 | 7.31 | 7.36 | 7.41 |
| Open Circuit Voltage | V _{oc} (V) | 35.70 | 35.90 | 36.10 | 36.30 | 37.00 | 37.30 | 37.60 | 37.80 |
| Short Circuit Current | I _{sc} (A) | 7.50 | 7.57 | 7.63 | 7.70 | 7.82 | 7.86 | 7.90 | 7.94 |

* Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Mechanical Data

| | |
|---------------------------------|--|
| Solar Cell Type | Poly 156.75×156.75mm (6 inches) |
| Number of Cells | 60 Cells (6×10) |
| Dimensions of Module L*W*H (mm) | 1658×992×6mm |
| Weight (kg) | 23kg |
| Front Side Glass | High transparency solar glass 2.5mm (0.13 inches) |
| Back Side Glass | Float solar glass 2.5mm (0.13 inches) |
| J-Box | IP68 Rated |
| Cable | 4.0mm ² (0.006 inches ²), length of '+': 225mm, length of '-': 75mm |
| Wind/ Snow Load | 2400Pa/5400Pa* |
| Connector | MC4 Compatible |

* For more details please check the installation manual of GCLSI

Temperature Ratings

| | |
|---|------------|
| Nominal Operating Cell Temperature (NOCT) | 44±2°C |
| Temperature Coefficient of I _{sc} | +0.050%/°C |
| Temperature Coefficient of V _{oc} | -0.30%/°C |
| Temperature Coefficient of P _{max} | -0.39%/°C |

Packaging Configuration

| | |
|--------------------------|------------|
| Module per box | 33 pieces |
| Module per 40' container | 858 pieces |



Maximum Ratings

| | |
|-------------------------|-----------|
| Operational Temperature | -40~+85°C |
| Maximum System Voltage | 1500V DC |
| Max Series Fuse Rating | 15A |


Optional

Connector: ☐ Original MC4


Module Dimension



U-I Curve at Different Temperature (275W)



U-I/P-U Curve at Different Irradiation (275W)



CAUTION: READ INSTALLATION MANUAL BEFORE USING THE PRODUCT



Contact Us for More Information

website: en.gclsi.com email: gclsisales@gclsi.com